Printing date 06.08.2006 Reviewed on 24.07.2006

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: n-hexane

· Manufacturer/Supplier:

Petrochem Middle East FZE PO Box 17028,

Jebel Ali Free Zone

Dubai, UAE

Ph +971 4 8839222; Fax +971 4 8834133

· Further information obtainable from: Product safety department.

2 Composition/information on ingredients

- · Chemical characterization:
- · CAS No. Description

110-54-3 n-hexane

- · Identification number(s)
- · EINECS Number: 203-777-6
- · EU Number: 601-037-00-0

3 Hazards identification

· Hazard description:







Repr. Cat. 3 Xn Harmful

F Highly flammable

N Dangerous for the environment

- · Information concerning particular hazards for human and environment:
- R 11 Highly flammable.
- R 38 Irritating to skin.
- R 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R 62 Possible risk of impaired fertility.
- R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 65 Harmful: may cause lung damage if swallowed.
- R 67 Vapours may cause drowsiness and dizziness.

4 First aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 2)



Printing date 06.08.2006 Reviewed on 24.07.2006

Trade name: n-hexane

· Protective equipment: No special measures required.

(Contd. of page 1)

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling:

Protect from ignition. Wear protective clothing and use approved respirator equipment. Absorb spilled material in an absorbent recommended for solvent spills and remove to a safe location for disposal by approved methods. If released to the environment, comply with all regulatory notification requirements.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 3)



Printing date 06.08.2006 Reviewed on 24.07.2006

Trade name: n-hexane

(Contd. of page 2)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9	Ph	ysi	cal	ana	C	iemi	ical	pro	pert	ies

· General Information						
Form:	Fluid					
Colour:	Colourless					
Odour:	Characteristic					
· Change in condition						
Melting point/Melting range:						
Boiling point/Boiling range:	69°C					
· Flash point:	-26°C					
· Ignition temperature:	240°C					
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixture are possible.					
· Explosion limits:						
Lower:	1.2 Vol %					
Upper:	7.4 Vol %					
· Vapour pressure at 20°C:	160 hPa					
· Density at 20°C:	0.66 g/cm³					
· Solubility in / Miscibility with water at 20°C:	0.1 g/l					



Printing date 06.08.2006 Reviewed on 24.07.2006

Trade name: n-hexane

(Contd. of page 3)

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

Danger code (Kemler): 33
UN-Number: 1208
Packaging group: II
Hazard label: 3

(Contd. on page 5)



Printing date 06.08.2006 Reviewed on 24.07.2006

Trade name: n-hexane

(Contd. of page 4)

· Description of goods: 1208 HEXANES

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1208
· Label 3
· Packaging group: II
· EMS Number: F-E,S-D

· Proper shipping name: HEXANES

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1208 · Label 3 · Packaging group: II

· Proper shipping name: HEXANES

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Repr. Cat. 3

Xn Harmful

F Highly flammable

N Dangerous for the environment

· Risk phrases:

- 11 Highly flammable.
- 38 Irritating to skin.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 62 Possible risk of impaired fertility.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.
- 29 Do not empty into drains.



Printing date 06.08.2006 Reviewed on 24.07.2006

Trade name: n-hexane

(Contd. of page 5)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department.
- · Contact: Terminal Manager

JAE -